



# New Product Information

## 5 models are added on line-up for Sport ZERO-3S!!



[Recommended for...]

- who drive on town mainly, but enjoy sporty driving at circuit on holiday.
- who drive on circuit with high-grip radial tire.
- who enjoy sporty driving for long-hours.

### Newly developed 24steps needle valve type adjustment

Securing wide range of damping adjustment from Circuit to town use while corresponding precise setting for sporty driving.

### Newly developed! Mono-tube shock absorber using large calibre piston.

It generates damping force smoothly, and it has suitable structure for motorsport as inside oil has well heat radiation which prevents overheating.

### High strength, High quality coilover kit emphasising "Rigidity".

With using high-rigidity steel bracket, this coilover secure durability from strong input from tyres. Also welding bracket with high-strength rib is applied.

#### [Major specification]

24steps damping, needle valve adjusting, overall length adjusting, Strut type: inverted shock absorber/Wishbone type: Unturned shock absorber

Upper mount is attached(except some model) Strut type: Front pillow-ball type, rear Aluminium strength rubber type/ Wishbone type: Aluminium strength rubber type



This product is rebuildable

Applicable model/series	Part No.	Price(excl.tax)	height adjustable range	SP rate(*1)	U/M	Height adjusting	D.O.R.
<b>TOYOTA</b>							
Mark X	GRX120	198 63S CN	¥198,000	F -55 ~ 0mm R -80 ~ 0mm	F 14k (11,12,16,18) R 6k (5,7,8,9,10)	A-RG	Overall length Early Sep.
<b>NISSAN</b>							
Silvia	S15	223 63S CN	¥228,000	F -70 ~ 0mm R -65 ~ 0mm	F 7k (8,9,10) R 4k (3,5,5,6,7,8,)	P-AJ A-RG	Overall length Early Sep.
<b>MITSUBISHI</b>							
Lancer Evolution	CT9A	564 63S CN	¥228,000	F -60 ~ 0mm R -70 ~ 0mm	F 8k (6,7,9,10,11,12) R 5k (4,6,7,8,9,10)	P-AJ A-RG	Overall length Early Sep.
<b>SUBARU</b>							
Impreza WRX	GVB	692 63S CN	¥228,000	F -50 ~ 0mm R -55 ~ -5mm	F 8k (7,9,10,11,12) R 7k (8,9,10,11)	P-AJ A-RG	Overall length on sale
Legacy B4	BL5	685 63S CN	¥228,000	F -50 ~ 0mm R -35 ~ 0mm	F 7k (8,9,10,11,12) R 7k (8,9,10)	P-AJ A-RG	Overall length Early Sep.

\* U/M=Upper mount,P-AJ=Adjustable pillow A-RG=Fixed aluminium strength rubber

\*1: Changing spring rate is available with no charge at its order.Choose the rate from ( ).

Contact CARROSSER Co.,Ltd. TEL +81 (27) 352 3578 FAX +81 (27) 352 1919

