



New Product Information

Additional on line up for high-grade coil over kit Compact ZERO2

The character of Compact ZERO 2

The dumping force is adjustable by 5steps on Front/8steps on Rear. It's adopted rotary valve which offer you easy(just one click) and accurate adjustment.

It offer wider setting range for competition driving, so you can custom the setting as each stage. Also you can enjoy driving on town with soft setting.


The ride feeling is still kept even you change the ride-height. It adopt overall-length adjustable system. Enable to individual pre-load adjust.

Ride-height adjustable area is worked anti-rust special coating.

It's adopted newly developed shock absorber for Compact Zero.

It's adopted high-strengthen bracket which is made by dedicated metal mol.

Changing Front spring rate is available on demand at order(within available range).



TOYOTA

Model	Series	Part.No.	Price(excl.tax)	Height adjustable range	SP rate(*4)	Upper mount	Re.	
Vitz	NCP91	900 60L CB	¥160,000	F	-70 ~ 0 mm	7(6) K	Without Upper mount	*1
				R	-40 ~ -15 mm	3.3 K		

SUZUKI

Swift	ZC11S	616 60L CB	¥166,000	F	-50 ~ 0 mm	7(6,8,9,10) K	Without Upper mount	*2
	ZC31S			R	-60 ~ -30 mm	4.0 K		

MITSUBISHI

Colt (including Ver.R)	Z21A,Z25A, Z27AG	524 60L CN	¥176,000	F	-60 ~ 0 mm	6(5,7,8) K	Adjustable pillow upper	*3
				R	-45 ~ -10 mm	3.3 K	Without Upper mount	

MAZDA

Demio	DE3FS	438 60L CN	¥176,000	F	-70 ~ 0 mm	6(5,7,8) K	Fixed pillow upper
	DE5FS			R	-70 ~ -30 mm	3.0 K	Without Upper mount

*1:Toyota Ist(NSP110) is applicable *2:The data is based on ZC31S *3: The data is based on Version R Z27AG

*4: () is default changeable range

Contact Carosser.co.,ltd TEL +81 (27) 352 3578 FAX +81 (27) 352 1919

