

New Product Information

TOYOTA GR YARIS GXPA16 street ZERO A NEW RELEASE



Product Image



Set ride quality according to the road condition.

Red street series top model

- 40-step damping force adjustment
- Double tapped full height adjustment
- CPRV (pressure optimization valve)
Improves ride comfort and steering stability when adjusting



«Applicable Vehicle»
TOYOTA GR YARIS GXPA16



- 40-step front and rear damping force adjustment.
- Double tapped full height adjustment type that does not compromise the suspension stroke.
- Twin tube shock absorber that provides a mild ride.
- Front camber adjustment option. (Adjustment of knuckle bracket eccentric bolt)
- Reliable domestic production, factory is ISO9001 certified, and meets ASEA standards.
- Optional spring rates available when ordering. *Free when ordering
- One year or 10,000km warranty (*1)

street ZERO A 40-step damping force adjustment/double tapped full height adjustment ※NOT compatible with e-con2

TYPE	Product Number	Price excl tax	Recommended vehicle height adjustment width *3	Spring *4	U/M *	Height adjustment mechanism	JAN Code	Release Date
Standard (Fixed Camber)	1C7 61N CB	¥150,000	F -35～-15mm	F 6K (7,8)	—	Double tapped	4996338111920	February
			R -40～-10mm	R 6K (7,8)	—	Spacer Screw		
	1C7 61N CN	¥185,000	F -35～-15mm	F 6K (7,8)	PRG	Double tapped	4996338112699	April
Front Adjustable camber *2	1C7 61N CP	¥205,000	F -35～-15mm	F 6K (7,8)	PRG	Double tapped	4996338112712	April
			R -40～-10mm	R 6K (7,8)	PRG	Spacer Screw		
	1C7 61N CBD	¥155,000	F -35～-15mm	F 6K (7,8)	—	Double tapped	4996338111937	February
			R -40～-10mm	R 6K (7,8)	—	Spacer Screw		
	1C7 61N CND	¥190,000	F -35～-15mm	F 6K (7,8)	PRG	Double tapped	4996338112705	April
			R -40～-10mm	R 6K (7,8)	—	Spacer Screw		
	1C7 61N CPD	¥210,000	F -35～-15mm	F 6K (7,8)	PRG	Double tapped	4996338112729	April
			R -40～-10mm	R 6K (7,8)	PRG	Spacer Screw		

※ Vehicles equipped with Toyota Safety Sense and preventive safety equipment, malfunction may occur due to decrease in vehicle height. Please note that we are not responsible for any malfunction caused by installing this product.

*U/M Upper Mount - =Upper mountless, PRG = Pillow ball fixed upper mount

*1 Apply with the user registration postcard included with the product. *2 Front camber can be adjusted with knuckle eccentric bolt. (included)

*3 Maximum height adjustment width

F:-70～-5mm/ R:-40～-10mm

The maximum height adjustment width is the calculation limit value, and actual installation and running confirmation are not performed. In addition, it may not be applicable to security stand.

*4 () Changeable rates when purchasing.

Various information can be downloaded from the download page of the Cusco website! ⇒

Download link URL <http://www.cusco.co.jp/download/>

«Contact» Carrosse Co., Ltd. TEL (027)352-3578 FAX (027)352-1919



<http://www.cusco.co.jp/>