

CUSCO ANTI-SWAY BAR

Car Model

Attachment Position	OUTER DIAMETER	PARTS No.	Ratio with Standard	Remarks
---------------------	----------------	-----------	---------------------	---------

MITSUBISHI

LANCER Evo.IV, V, VI CN9A,CP9A

FRONT	25	560 311 A25	135%	Including Sutabilizer bushes
REAR	23	560 311 BJ23	108%/122%/138%	Three-step adjustment, Including Sutabilizer bushes
REAR	18	560 311 BJ18	33% 50% 66%	Three-step adjustment, For sutanderd Sutabilizer bushes, For Gravel

LANCER Evo.VII, VIII CT9A

FRONT	25	564 311 A25	123%	For standard Sutabilizer bushes and standard Sutabilizer brackets
FRONT	21	564 311 A21	64%	For standard Sutabilizer bushes and standard brackets, For gravel
REAR	23	560 311 BJ23	103%/115%/125%	Three-step adjustment, Including Sutabilizer bushes
REAR	18	560 311 BJ18	30% 46% 57%	Three-step adjustment, For standard Sutabilizer bushes, For gravel

MIRAGE

CJ4A(Except wearing 15inch wheel vehicles)

FRONT	17	550 311 AJ17	123%/138%	Two-step adjustment, For standard Sutabilizer bushes,
FRONT	15	550 311 AJ15	62%/69%	Two-step adjustment, For standard Sutabilizer bushes, For gravel
REAR	14	550 311 BJ14	65% 76%/105%	Three-step adjustment, For standard Sutabilizer bushes, For gravel
REAR	16	550 311 BJ16	129%/158%/200%	Three-step adjustment, For standard Sutabilizer bushes

Adjustabl stabilizer brackets for LANCER Evo.V(CP9A) #561 315 A ¥4,800

Adjustabl stabilizer brackets for LANCER Evo. VI, VII, VIII(CP9A,CT9A,) #560 315 A ¥4,800